

- Peterson, D. (2025, February 7). *Global Semiconductor Sales Increase 19.1% in 2024; Double-Digit Growth Projected in 2025*. Semiconductor Industry Association.  
<https://www.semiconductors.org/global-semiconductor-sales-increase-19-1-in-2024-double-digit-growth-projected-in-2025/>
- Poduje, N., Kerr, W., & Turner, K. T. (2010). Inspection of Bonded Interfaces Using Scanning Infrared Interferometry. *ECS Transactions*, 33(4), 537.  
<https://doi.org/10.1149/1.3483545>
- Rudack, A. C., Kong, L. W., & Baker, G. G. (2010). Infrared microscopy for overlay and defect metrology on 3D-interconnect bonded wafers. *2010 IEEE/SEMI Advanced Semiconductor Manufacturing Conference (ASMC)*, 347–352.  
<https://doi.org/10.1109/ASMC.2010.5551481>
- Kuo, Y.-L., Lin, Y.-C., Lin, Y.-T., Huan, H.-S., & Su, D. (2004). Failure analysis of IMC cracking and voiding induced by molding compound voids in advanced wire bonding packages. *Proceedings of the 11th International Symposium on the Physical and Failure Analysis of Integrated Circuits. IPFA 2004 (IEEE Cat. No.04TH8743)*, 221–224.  
<https://doi.org/10.1109/IPFA.2004.1345603>
- Said, A. F., Bennett, B. L., Karam, L. J., Siah, A., Goodman, K., & Pettinato, J. S. (2012). Automated Void Detection in Solder Balls in the Presence of Vias and Other Artifacts. *IEEE Transactions on Components, Packaging and Manufacturing Technology*, 2(11), 1890–1901. *IEEE Transactions on Components, Packaging and Manufacturing Technology*. <https://doi.org/10.1109/TCPMT.2011.2182613>
- Jourdon, J., Lhostis, S., Moreau, S., Bresson, N., Salomé, P., & Frémont, H. (2019). Evaluation of Hybrid Bonding Interface Quality by Contact Resistivity Measurement. *IEEE Transactions on Electron Devices*, 66(6), 2699–2703. *IEEE Transactions on Electron Devices*. <https://doi.org/10.1109/TED.2019.2910528>

IAI America, Inc. (2012). *Tabletop robot TT: Product brochure (Catalog No. CJ0082-1A-UST-3-0612)*. IAI America, Inc. <https://www.intelligentactuator.com>

Google. (2021). *English: Google Colaboratory SVG (vector) Logo, color on transparent background* [Graphic]. <https://colab.research.google.com> Google Colab top-left logo. [https://commons.wikimedia.org/wiki/File:Google\\_Colaboratory\\_SVG\\_Logo.svg](https://commons.wikimedia.org/wiki/File:Google_Colaboratory_SVG_Logo.svg)

Poduje, N., Kerr, W., & Turner, K. T. (2010). Inspection of Bonded Interfaces Using Scanning Infrared Interferometry. *ECS Transactions*, 33(4), 537. <https://doi.org/10.1149/1.3483545>

Kuo, Y.-L., Lin, Y.-C., Lin, Y.-T., Huan, H.-S., & Su, D. (2004). Failure analysis of IMC cracking and voiding induced by molding compound voids in advanced wire bonding packages. *Proceedings of the 11th International Symposium on the Physical and Failure Analysis of Integrated Circuits. IPFA 2004 (IEEE Cat. No.04TH8743)*, 221–224. <https://doi.org/10.1109/IPFA.2004.1345603>

Siddiqui, J., Ortega, J., & Albus, B. (2017). On the relationship between semiconductor manufacturing volume, yield, and reliability. *2017 IEEE International Reliability Physics Symposium (IRPS)*, SR-1.1-SR-1.5. <https://doi.org/10.1109/IRPS.2017.7936409>

Rudack, A. C., Kong, L. W., & Baker, G. G. (2010). Infrared microscopy for overlay and defect metrology on 3D-interconnect bonded wafers. *2010 IEEE/SEMI Advanced Semiconductor Manufacturing Conference (ASMC)*, 347–352. <https://doi.org/10.1109/ASMC.2010.5551481>

Allen, R. A., Rudack, A., Read, D., & Baylies, W. (2010). Intercomparison of Methods for Detecting and Characterizing Voids in Bonded Wafer Pairs. *ECS Transactions*, 33(4), 581. <https://doi.org/10.1149/1.3483550>

Kasaya, K., Yoshikuni, Y., & Ishii, H. (1996). Measurements of a semiconductor waveguide using a low-coherence interferometric reflectometer. *IEEE Photonics Technology Letters*, 8(2), 251–253. *IEEE Photonics Technology Letters*.  
<https://doi.org/10.1109/68.484257>

Takahashi, A., & Ishida, Y. (2004). *Method for manufacturing semiconductor device* (Japan Patent Office Patent).  
<https://patents.google.com/patent/JP2004311603A/en?q=JP2004311603A.pdf>

Th, E. K., Hao, J. Y., Ding, J. P., Li, Q. F., Chan, W. L., Ho, S. C., Huang, H. M., & Jiang, Y. J. (2009). Encapsulation challenges for wafer-level packaging. *2009 11th Electronics Packaging Technology Conference*, 903–908.  
<https://doi.org/10.1109/EPTC.2009.5416414>

Baker, G. G. (2010). Infrared microscopy for overlay and defect metrology on 3D-interconnect bonded wafers. *2010 IEEE/SEMI Advanced Semiconductor Manufacturing Conference (ASMC)*, 347–352.  
<https://doi.org/10.1109/ASMC.2010.5551481>

A. F. Said, B. L. Bennett, L. J. Karam and J. Pettinato, Robust automatic void detection in solder balls, *2010 IEEE International Conference on Acoustics, Speech and Signal Processing*, Dallas, TX, USA, 2010, pp. 1650-1653, <https://doi.org/10.1109/ICASSP.2010.549552>

